




Артикул №	1242	2473	1702
Стандарт	DIN 6539		
Режущий материал	Цельный тв. сплав		
Группа применения тв.сплава	K/P		
Покрытие			
Тип	RT 100 U	RT 100 U	RT 100 F
Глубина сверления:	3xD	3xD	3xD
Направление резания	правое	правое	правое
Допуск	m7	m7	m7
Группа скидок	121	121	121
Техническая информация на стр.	121	122	122

Сверла Ratio



d1		l1	l2
мм	дюйм	мм	мм
8,730	11/32	84,00	40,00
8,800		84,00	40,00
8,900		84,00	40,00
9,000		84,00	40,00
9,100		84,00	40,00
9,130	23/64	84,00	40,00
9,200		84,00	40,00
9,300		84,00	40,00
9,400		84,00	40,00
9,500		84,00	40,00
9,520	3/8	89,00	43,00
9,600		89,00	43,00
9,700		89,00	43,00
9,800		89,00	43,00
9,900		89,00	43,00
9,920	25/64	89,00	43,00
10,000		89,00	43,00
10,100		89,00	43,00
10,200		89,00	43,00
10,300		89,00	43,00
10,320	13/32	89,00	43,00
10,400		89,00	43,00
10,500		89,00	43,00
10,600		89,00	43,00
10,700		95,00	47,00
10,720	27/64	95,00	47,00
10,800		95,00	47,00
10,900		95,00	47,00
11,000		95,00	47,00
11,100		95,00	47,00
11,110	7/16	95,00	47,00
11,200		95,00	47,00
11,300		95,00	47,00
11,400		95,00	47,00
11,500		95,00	47,00
11,510	29/64	95,00	47,00

Цена/шт. в ЕВРО		
●		●
●	○	○
○		●
●	○	○
●	○	○
●		○
●		
●	○	●
●		●
●		●
●		●
○		●
●		●
●	○	
●		●
●		●
●	○	
●		●
●		●
●		●
○		○
●	○	○
●		○
●		○

C TiCN

Cb Carbo

D Cristall

F FIRE/nanoFIRE

P AlCrN

S TiN

S+ TiN+

M MolyGlide

Y Signum