


Спиральные сверла, средние

Спиральные сверла
с цилиндрическим
хвостовиком

Артикул №	205	206	207	208	209	210
Стандарт	DIN 338					
Режущий материал	HSS					
Покрытие						
Тип	N	H	W	N	H	W
Направление резания	правое	правое	правое	левостор.	левостор.	левостор.
Допуск	h8	h8	h8	h8	h8	h8
Группа скидок	130	134	134	134	134	138
Техническая информация на стр.	144	144	144	144	144	145



d1		l1	l2
мм	дюйм	мм	мм
0,570		24,00	7,00
0,575		24,00	7,00
0,580		24,00	7,00
0,590		24,00	7,00
0,600		24,00	7,00
0,610		26,00	8,00
0,620		26,00	8,00
0,630		26,00	8,00
0,640		26,00	8,00
0,650		26,00	8,00
0,660		26,00	8,00
0,670		26,00	8,00
0,675		28,00	9,00
0,680		28,00	9,00
0,690		28,00	9,00
0,700		28,00	9,00
0,710		28,00	9,00
0,720		28,00	9,00
0,730		28,00	9,00
0,740		28,00	9,00
0,750		28,00	9,00
0,760		30,00	10,00
0,770		30,00	10,00
0,775		30,00	10,00
0,780		30,00	10,00
0,790	1/32	30,00	10,00
0,800		30,00	10,00
0,810		30,00	10,00
0,820		30,00	10,00
0,825		30,00	10,00
0,830		30,00	10,00
0,840		30,00	10,00
0,850		30,00	10,00
0,860		32,00	11,00
0,870		32,00	11,00
0,880		32,00	11,00
0,890		32,00	11,00
0,900		32,00	11,00
0,910		32,00	11,00

Цена/шт. в ЕВРО					
●	●	●	●		
●			●	○	
●			●	○	○
●	●	●	●	●	●
●		●	●	●	○
●	●	●	○	○	○
●	○	●	●	●	
●	●	●	●	●	○
●	●	●	○	●	
○			●	○	
●	●		●	○	
●	○		●	●	●
●	●	●	●	●	○
●	●	●	○	○	●
●	●		●	○	●
●	●	●	●	○	○
●	●	●	●	●	○
●	●		○		○
●	●	●	○	○	
●	●	●	●	○	○
●	●	○	●	●	●
●	●	●	●	●	○
●	○	●	●	○	○
●	●	○	●	○	○
●	●	●	○	○	○
●	●	●	●	●	○
●	●	●	●	●	○

 без покрытия
 обработка паром
 азотирование ленточек
 азотирование
 золотисто-коричневое
 TiAlN
 TiAlN nanoA
 TiAlN SuperA