


Спиральные сверла, средние

Спиральные сверла
с цилиндрическим
хвостовиком

Артикул №	205	206	207	208	209	210
Стандарт	DIN 338					
Режущий материал	HSS					
Покрытие						
Тип	N	H	W	N	H	W
Направление резания	правое	правое	правое	левостор.	левостор.	левостор.
Допуск	h8	h8	h8	h8	h8	h8
Группа скидок	130	134	134	134	134	138
Техническая информация на стр.	144	144	144	144	144	145



d1		l1	l2
мм	дюйм	мм	мм
0,920		32,00	11,00
0,930		32,00	11,00
0,940		32,00	11,00
0,950		32,00	11,00
0,960		34,00	12,00
0,970		34,00	12,00
0,980		34,00	12,00
0,990		34,00	12,00
1,000		34,00	12,00
1,010		34,00	12,00
1,020		34,00	12,00
1,030		34,00	12,00
1,040		34,00	12,00
1,050		34,00	12,00
1,060		34,00	12,00
1,070		36,00	14,00
1,080		36,00	14,00
1,090		36,00	14,00
1,100		36,00	14,00
1,110		36,00	14,00
1,120		36,00	14,00
1,130		36,00	14,00
1,140		36,00	14,00
1,150		36,00	14,00
1,160		36,00	14,00
1,165		36,00	14,00
1,170		36,00	14,00
1,180		36,00	14,00
1,190	3/64	38,00	16,00
1,200		38,00	16,00
1,210		38,00	16,00
1,220		38,00	16,00
1,230		38,00	16,00
1,240		38,00	16,00
1,250		38,00	16,00
1,260		38,00	16,00
1,270		38,00	16,00
1,280		38,00	16,00
1,290		38,00	16,00

Цена/шт. в ЕВРО					
●	●		●	●	
●	●			○	
●					
●	●	●	●	●	○
●	●	●	●	●	
●	●	●	●	○	○
●	○	●	●		○
●	●	●	●	●	○
●	●	●	●	●	●
●	●	●	●	○	
●	●	●	●	○	○
●	●	●	●	●	
●	●	●	●	○	○
●	●	●	●	○	
●	●	●	●	●	○
●	●	●	○	●	
●	●	●	○	●	●
●	●	○	●	○	○
●	○	●	●	○	
●	●	○	●	●	●
●	●	●	●	○	
●	●	●	●	○	○
●	●	●	●	○	
●	●	○	●	○	○
●	●	●	●	●	●
●	●	○	●	○	○
●	●	●	●	○	
●	●	●	○	○	○
●	●	●	●	○	
●	●	●	●	○	
●	●	●	●	○	○
●	●	●	●	○	
●	●	●	●	○	
●	●	●	●	○	○
●	●	●	●	○	

 без покрытия
 обработка паром
 азотирование ленточек
 азотирование
 золотисто-коричневое
 TiAlN
 TiAlN nanoA
 TiAlN SuperA