




Спиральные сверла, средние

Спиральные сверла
с цилиндрическим
хвостовиком

Артикул №	205	206	207	208	209	210
Стандарт	DIN 338					
Режущий материал	HSS					
Покрытие						
Тип	N	H	W	N	H	W
Направление резания	правое	правое	правое	левостор.	левостор.	левостор.
Допуск	h8	h8	h8	h8	h8	h8
Группа скидок	130	134	134	134	134	138
Техническая информация на стр.	144	144	144	144	144	145



d1				Цена/шт. в ЕВРО					
мм	дюйм	мм	мм						
1,300		38,00	16,00	●	●	●	●	●	○
1,305		38,00	16,00						
1,310		38,00	16,00	●			○		
1,320		38,00	16,00	●	●		●	○	○
1,330		40,00	18,00	●	●	●			
1,340		40,00	18,00	●					
1,350		40,00	18,00	●	●	●	●		
1,360		40,00	18,00	●					
1,370		40,00	18,00	●	●				
1,380		40,00	18,00	●	●	●	○	○	
1,390		40,00	18,00	●			●		
1,400		40,00	18,00	●	●	●	●		●
1,410		40,00	18,00	●			○		
1,420		40,00	18,00	●	●	●	●		
1,430		40,00	18,00	●	●	●	●		
1,440		40,00	18,00	●	●	○			
1,450		40,00	18,00	●	●	●	●	●	●
1,460		40,00	18,00	●					
1,465		40,00	18,00				○		
1,470		40,00	18,00	●	●		●		
1,480		40,00	18,00	●	●			○	○
1,485		40,00	18,00						
1,490		40,00	18,00	●	●		○		
1,500		40,00	18,00	●	●	●	●	●	●
1,510		43,00	20,00	●		●	●		
1,520		43,00	20,00	●	●	●	○	○	○
1,530		43,00	20,00	●	●	●	○		
1,540		43,00	20,00	●	○	●			○
1,550		43,00	20,00	●	●	●	●	●	○
1,560		43,00	20,00	●			○		
1,570		43,00	20,00	●		●	○		
1,580		43,00	20,00	●		○	○		○
1,590	1/16	43,00	20,00	●	●	○	●		
1,600		43,00	20,00	●	●	●	●	○	○
1,610		43,00	20,00	●		●	○		
1,620		43,00	20,00	●	●		○	○	
1,630		43,00	20,00	●		●	○	○	○
1,640		43,00	20,00	●			●		
1,650		43,00	20,00	●	●	●	●		

○ без покрытия ○ обработка паром ● азотирование ленточек ● азотирование ● золотисто-коричневое A TiAlN a TiAlN nanoA A TiAlN SuperA