


Спиральные сверла, средние

Спиральные сверла
с цилиндрическим
хвостовиком

Артикул №	205	206	207	208	209	210
Стандарт	DIN 338					
Режущий материал	HSS					
Покрытие						
Тип	N	H	W	N	H	W
Направление резания	правое	правое	правое	левостор.	левостор.	левостор.
Допуск	h8	h8	h8	h8	h8	h8
Группа скидок	130	134	134	134	134	138
Техническая информация на стр.	144	144	144	144	144	145



d1		l1	l2
мм	дюйм	мм	мм
1,660		43,00	20,00
1,670		43,00	20,00
1,680		43,00	20,00
1,690		43,00	20,00
1,700		43,00	20,00
1,710		46,00	22,00
1,720		46,00	22,00
1,730		46,00	22,00
1,740		46,00	22,00
1,750		46,00	22,00
1,760		46,00	22,00
1,770		46,00	22,00
1,780		46,00	22,00
1,790		46,00	22,00
1,800		46,00	22,00
1,810		46,00	22,00
1,820		46,00	22,00
1,830		46,00	22,00
1,840		46,00	22,00
1,850		46,00	22,00
1,860		46,00	22,00
1,870		46,00	22,00
1,880		46,00	22,00
1,890		46,00	22,00
1,900		46,00	22,00
1,910		49,00	24,00
1,920		49,00	24,00
1,930		49,00	24,00
1,940		49,00	24,00
1,950		49,00	24,00
1,960		49,00	24,00
1,970		49,00	24,00
1,980	5/64	49,00	24,00
1,990		49,00	24,00
2,000		49,00	24,00
2,010		49,00	24,00
2,020		49,00	24,00
2,030		49,00	24,00
2,040		49,00	24,00

Цена/шт. в ЕВРО					
●		●	●	●	○
●	●		●	●	
●		○	●		
●	●	●	●	●	○
●			○		
●	●		●	○	
●	●		○	○	
●		●	●	●	○
●		●	○		
●	●	●	○		
●	●	○	●	●	
●	●	●	●	●	●
●	●	●	●	●	
●	●	●	●	○	
●		●	●	●	
●	●	●	○	●	○
●			●	○	
●	●	●		○	
●	●	●	●	●	○
●	●	○	○	○	
●	○		●	○	○
●	●	●	●	○	
●	●	●	●	●	●
●	○		○	●	
●	●	●	●	●	

 без покрытия
 обработка паром
 азотирование ленточек
 азотирование
 золотисто-коричневое
 TiAlN
 TiAlN nanoA
 TiAlN SuperA