

High Performance CARBIDE DRILLS

GUHRING
Select

GUHRING
Select

GUHRING
Select

GUHRING
Select



SERIES	730	2463	1702	1242	1184	5514	5741	8524	8510	5510	5610	2477	8520
Style	Type N	Type N	RT 100 F	RT 100 U	RT 100 U	RT 100 U	RT 100 US	RT 100 HF	RT 100 VA	RT 100 U	RT 100 U	RT 100 "X"	RT 100 HF
Point Angle	118°	118°	140°	140°	140°	140°	140°	140°	140°	140°	140°	140°	140°
Length	3 x D	3 x D	3 x D	3 x D	3 x D	3 x D	3 x D	3 x D	3 x D	3 x D	3 x D	3 x D	3 x D
Shank													
Coolant													
Carbide Grade	DK120	DK120	DK460UF	DK460UF	DK460UF	DK460UF	DK460UF	DK460UF	DK460UF	DK460UF	DK460UF	DK460UF	DK460UF
Surface Finish	○	●	●	●	●	●	●	●	●	●	●	●	●
Std. Dia. Range mm	0.50- 16.00	1.00-16.00	3.00- 15.00	3.00- 16.00	3.00- 20.00	3.00- 20.00	3.00- 12.70	3.00- 20.00	3.00-20.00	3.00- 20.00	3.00-20.00	3.00- 20.00	3.00- 20.00
Std. Dia. Range In.	0.0197- 0.6299	0.0394- 0.6299	0.1181- 0.5906	0.1181- 0.6299	0.1181- 0.7874	0.1181- 0.7874	0.1181- 0.5000	0.1181- 0.7874	0.1181- 0.7874	0.1181- 0.7874	0.1181- 0.7874	0.1181- 0.7874	0.1181- 0.7874
Catalog Page	197	222	219	212	208	260	290	316	307	253	283	226	311
Tech Data Page	454	464	463	461	459	483	493	503	501	481	489	465	502

GUHRING
Select

GUHRING
Select



SERIES	5512	5612	4044	6502	5746	8522	2601	2602	5525
Style	RT 100 U	RT 100 U	RT 100 "X"	RT 100 R	RT 100 US	RT 100 HF	GT 100	GT 100	RT 100 C
Point Angle	140°	140°	140°	Special	140°	140°	130°	130°	140°
Length	7 x D	7 x D	7 x D	7 x D	7 x D	7 x D	8 x D	8 x D	12 x D
Shank									
Coolant									
Carbide Grade	DK460UF	DK460UF	DK460UF	DK255F	DK460UF	DK460UF	DK460UF	DK460UF	DK460UF
Surface Finish	●	●	●	●	●	●	○	●	●
Std. Dia. Range mm	3.00- 20.00	3.00- 20.00	3.00- 20.00	3.00- 20.00	4.00- 12.70	3.00- 16.00	3.17- 12.70	3.17- 12.70	3.00- 20.00
Std. Dia. Range In.	0.1181- 0.7874	0.1181- 0.7874	0.1181- 0.7874	0.1181- 0.7874	0.1181- 0.5000	0.1181- 0.6299	0.1248- 0.5000	0.1248- 0.5000	0.1181- 0.7874
Catalog Page	257	287	250	303	294	315	230	231	277
Tech Data Page	482	490	479	498	494	503	467	468	487