
















# High Performance CARBIDE DRILLS

## RT 800 WP Inserts and Holders

SERIES						
Style	RT 800 WP Insert	RT 800 WP Insert	RT 800 WP Insert	RT 800 WP Holder	RT 800 WP Holder	RT 800 WP Holder
Point Angle	140°	140°	140°	N/A	N/A	N/A
Length	N/A	N/A	N/A	3 x D	5 x D	7 x D
Shank	N/A	N/A	N/A			
Coolant						
Carbide Grade	DK460UF	DK460UF	DK460UF	HSS	HSS	HSS
Surface Finish				Nickel	Nickel	Nickel
Std. Dia. Range mm	16.00- 40.50	16.00- 40.50	16.00- 40.50	N/A	N/A	N/A
Std. Dia. Range In.	0.6299- 1.5945	0.6299- 1.5945	0.6299- 1.5945	N/A	N/A	N/A
Catalog Page	246	246	246	248	248	248
Tech Data Page	468-469	456-457	466-467	N/A	N/A	N/A

## HT 800 WP Inserts

SERIES					
Style	HT 800 WP Insert	HT 800 WP Insert	HT 800 WP Insert	HT 800 WP Insert	HT 800 WP Insert
Point Angle	145°	140°	140°	140°	140°
Length	N/A	N/A	N/A	N/A	N/A
Shank	N/A	N/A	N/A	N/A	N/A
Coolant					
Carbide Grade	DK460UF	DK460UF	DK460UF	DK460UF	DK460UF
Surface Finish					
Std. Dia. Range mm	11.00- 25.50	11.00- 25.50	11.00- 25.50	11.00- 25.50	11.00- 25.50
Std. Dia. Range In.	0.4331- 1.0039	0.4331- 1.0039	0.4331- 1.0039	0.4331- 1.0039	0.4331- 1.0039
Catalog Page	244	238	238	238	238
Tech Data Page	N/A	475-478	475-478	475-478	475-478