















































Stub Length (3xD) Drills

											
Series	301	303	223	226	225	224	552	553	653	5520	730
Length	Micro	Micro (LH)	3xD	3xD (LH)	3xD	3xD	3xD	3xD (LH)	3xD	3xD	3xD
Shank											
Style	N	N	N	N	W	H	GT80	GT80	N	GU500DZ	N
Point Angle	118°	118°	118°	118°	130°	118°	130°	130°	118°	118°	118°
Coolant Fed											
Substrate	Cobalt	Cobalt	HSS	HSS	HSS	HSS	HSS	HSS	HSS	Cobalt	Carbide
Surface Finish											
Structural Steel	✓	✓	✓	✓			✓	✓	✓	✓	✓
Free-cutting steel	✓	✓	✓	✓	✓		✓	✓	✓	✓	✓
Unalloyed steels	✓	✓	✓	✓	✓		✓	✓	✓	✓	✓
Copper	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
Brass	✓	✓	✓	✓		✓	✓	✓	✓	✓	✓
Size range mm	0.05 - 1.92	0.13 - 1.85	0.40 - 31.75	0.50 - 44.45	1.00 - 20.00	0.90 - 22.00	1.00 - 20.00	1.00 - 20.00	0.50 - 28.50	1.00 - 14.29	0.50 - 16.00
Sizes page	111	113	90	98	96	94	152	155	176	267	197

