































Index - Pro-Line

Type	Helix angle	Number of teeth	Length	Tool description	Tool material Surface finish	Gurhing no.	Gurhing no.	Unit	Diameter Range	Page
						HA	HB			
UNI PRO end mills (2-fluted) with corner radius					carbide					
N	30°	2			FIREX®	3087		Inch	1/8 - 1/2	126
N	30°	2			Bright	3106		Metric	6 - 20	128
N	30°	2			FIREX®	3561		Metric	6 - 20	128
N	30°	2			FIREX®	3088		Inch	1/8 - 1/2	126
UNI PRO end mills (3-fluted)					carbide					
N	30°	3			FIREX®	3558	3719	Metric	2 - 16	131
N	30°	3			Bright	3168		Inch	1/8 - 1	130
N	30°	3			Bright	3307		Metric	2 - 20	131
N	30°	3			FIREX®	3170		Inch	1/8 - 1	130
N	30°	3			Super-A™	3868		Inch	1/8 - 1	130
N	30°	3			FIREX®	3677		Metric	2 - 20	131
N	30°	3			Bright	3169		Inch	3/16 - 1	130
N	30°	3			FIREX®	3171		Inch	3/16 - 1	130
N	30°	3			Super-A™	3869		Inch	3/16 - 1	130
N	30°	3			Bright	3314		Metric	3 - 20	131
N	30°	3			FIREX®	3680		Metric	3 - 20	131