


# Спиральные сверла, короткие

Сверла


Артикул №	8900
Стандарт	DIN 1897
Режущий материал	HSS
Покрытие	
Тип	N
Направление резания	правое
Допуск	h8
Группа скидок	101

Диапазон диаметров: 2,000 - 13,000


Затыловка: Конусная

Угол при вершине сверла: 118°

Подточка ≥Ø: 2,00 мм



d1 мм	d1 дюйм	l1 мм	l2 мм	Наличие на складе
2,000		38,000	12,000	●
2,100		38,000	12,000	●
2,200		40,000	13,000	●
2,300		40,000	13,000	●
2,400		43,000	14,000	●
2,500		43,000	14,000	●
2,600		43,000	14,000	●
2,700		46,000	16,000	●
2,800		46,000	16,000	●
2,900		46,000	16,000	●
3,000		46,000	16,000	●
3,100		49,000	18,000	●
3,170	1/8	49,000	18,000	●
3,200		49,000	18,000	●
3,300		49,000	18,000	●
3,400		52,000	20,000	●
3,500		52,000	20,000	●
3,600		52,000	20,000	●
3,700		52,000	20,000	●
3,800		55,000	22,000	●
3,900		55,000	22,000	●
4,000		55,000	22,000	●
4,100		55,000	22,000	●
4,200		55,000	22,000	●
4,300		58,000	24,000	●
4,400		58,000	24,000	●
4,500		58,000	24,000	●
4,600		58,000	24,000	●
4,700		58,000	24,000	●
4,760	3/16	62,000	26,000	●
4,800		62,000	26,000	●
4,900		62,000	26,000	●
5,000		62,000	26,000	●
5,100		62,000	26,000	●
5,200		62,000	26,000	●
5,300		62,000	26,000	●
5,400		66,000	28,000	●
5,500		66,000	28,000	●
5,600		66,000	28,000	●
5,700		66,000	28,000	●

 без покрытия/обработка паром