



Спиральные сверла, короткие

Артикул №	8904
Стандарт	DIN 1897
Режущий материал	HSCO
Покрытие	
Тип	GU 500
Направление резания	правое
Допуск	h8
Группа скидок	101

Диапазон диаметров: 2,000 - 13,000

Затыловка: Плоскостная

Угол при вершине сверла: 118°

Подточка $\geq \varnothing$: 2,00 мм

d1 мм	d1 дюйм	l1 мм	l2 мм	Наличие на складе
2,000		38,000	12,000	●
2,500		43,000	14,000	●
3,000		46,000	16,000	●
3,170	1/8	49,000	18,000	●
3,200		49,000	18,000	●
3,300		49,000	18,000	●
3,500		52,000	20,000	●
4,000		55,000	22,000	●
4,200		55,000	22,000	●
4,500		58,000	24,000	●
4,760	3/16	62,000	26,000	●
5,000		62,000	26,000	●
5,100		62,000	26,000	●
5,200		62,000	26,000	●
5,500		66,000	28,000	●
6,000		66,000	28,000	●
6,350	1/4	70,000	31,000	●
6,500		70,000	31,000	●
6,800		74,000	34,000	●
7,000		74,000	34,000	●
7,500		74,000	34,000	●
7,940	5/16	79,000	37,000	●
8,000		79,000	37,000	●
8,500		79,000	37,000	●
9,000		84,000	40,000	●
9,500		84,000	40,000	●
10,000		89,000	43,000	●
10,200		89,000	43,000	●
10,500		89,000	43,000	●
11,000		95,000	47,000	●
11,110	7/16	95,000	47,000	●
11,500		95,000	47,000	●
12,000		102,000	51,000	●
12,500		102,000	51,000	●
13,000		102,000	51,000	●