



Артикул №	8902
Стандарт	DIN 338
Режущий материал	HSS
Покрытие	
Тип	N
Направление резания	правое
Допуск	h8
Группа скидок	101

Диапазон диаметров: 1,000 - 13,000

Затыловка: Конусная

Угол при вершине сверла: 118°

Подточка ≥Ø: 1,00 мм



d1 мм	d1 дюйм	l1 мм	l2 мм	Наличие на складе
1,000		34,000	12,000	●
1,100		36,000	14,000	●
1,190	3/64	38,000	16,000	●
1,200		38,000	16,000	●
1,300		38,000	16,000	●
1,400		40,000	18,000	●
1,500		40,000	18,000	●
1,590	1/16	43,000	20,000	●
1,600		43,000	20,000	●
1,700		43,000	20,000	●
1,800		46,000	22,000	●
1,900		46,000	22,000	●
1,980	5/64	49,000	24,000	●
2,000		49,000	24,000	●
2,100		49,000	24,000	●
2,200		53,000	27,000	●
2,300		53,000	27,000	●
2,380	3/32	57,000	30,000	●
2,400		57,000	30,000	●
2,500		57,000	30,000	●
2,600		57,000	30,000	●
2,700		61,000	33,000	●
2,780	7/64	61,000	33,000	●
2,800		61,000	33,000	●
2,900		61,000	33,000	●
3,000		61,000	33,000	●
3,100		65,000	36,000	●
3,170	1/8	65,000	36,000	●
3,200		65,000	36,000	●
3,300		65,000	36,000	●
3,400		70,000	39,000	●
3,500		70,000	39,000	●
3,570	9/64	70,000	39,000	●
3,600		70,000	39,000	●
3,700		70,000	39,000	●
3,800		75,000	43,000	●
3,900		75,000	43,000	●
3,970	5/32	75,000	43,000	●
4,000		75,000	43,000	●