



Артикул №	8916
Стандарт	DIN 338
Режущий материал	HSS
Покрытие	
Тип	GT 100
Направление резания	правое
Допуск	h8
Группа скидок	101

Диапазон диаметров: 1,000 - 13,000

Затыловка: Конусная

Угол при вершине сверла: 130°

Подточка ≥Ø: 1,00 мм



d1 мм	l1 мм	l2 мм	Наличие на складе
1,000	34,000	12,000	●
1,500	40,000	18,000	●
2,000	49,000	24,000	●
2,500	57,000	30,000	●
3,000	61,000	33,000	●
3,300	65,000	36,000	●
3,500	70,000	39,000	●
4,000	75,000	43,000	●
4,200	75,000	43,000	●
4,500	80,000	47,000	●
5,000	86,000	52,000	●
5,500	93,000	57,000	●
6,000	93,000	57,000	●
6,500	101,000	63,000	●
6,800	109,000	69,000	●
7,000	109,000	69,000	●
7,500	109,000	69,000	●
8,000	117,000	75,000	●
8,500	117,000	75,000	●
9,000	125,000	81,000	●
9,500	125,000	81,000	●
10,000	133,000	87,000	●
10,200	133,000	87,000	●
10,500	133,000	87,000	●
11,000	142,000	94,000	●
11,500	142,000	94,000	●
12,000	151,000	101,000	●
12,500	151,000	101,000	●
13,000	151,000	101,000	●