


Артикул №	8918
Стандарт	DIN 340
Режущий материал	HSS
Покрытие	
Тип	GT 100
Направление резания	правое
Допуск	h8
Группа скидок	101

Диапазон диаметров: 1,000 - 13,000

Затыловка: Конусная

Угол при вершине сверла: 130°

Подточка ≥Ø: 1,00 мм



d1 мм	d1 дюйм	l1 мм	l2 мм	Наличие на складе
1,000		56,000	33,000	●
1,100		60,000	37,000	●
1,190	3/64	65,000	41,000	●
1,200		65,000	41,000	●
1,300		65,000	41,000	●
1,400		70,000	45,000	●
1,500		70,000	45,000	●
1,590	1/16	76,000	50,000	●
1,600		76,000	50,000	●
1,700		76,000	50,000	●
1,800		80,000	53,000	●
1,900		80,000	53,000	●
2,000		85,000	56,000	●
2,100		85,000	56,000	●
2,200		90,000	59,000	●
2,300		90,000	59,000	●
2,380	3/32	95,000	62,000	●
2,400		95,000	62,000	●
2,500		95,000	62,000	●
2,600		95,000	62,000	●
2,700		100,000	66,000	●
2,800		100,000	66,000	●
2,900		100,000	66,000	●
3,000		100,000	66,000	●
3,100		106,000	69,000	●
3,170	1/8	106,000	69,000	●
3,200		106,000	69,000	●
3,300		106,000	69,000	●
3,400		112,000	73,000	●
3,500		112,000	73,000	●
3,600		112,000	73,000	●
3,700		112,000	73,000	●
3,800		119,000	78,000	●
3,900		119,000	78,000	●
4,000		119,000	78,000	●
4,100		119,000	78,000	●
4,200		119,000	78,000	●
4,300		126,000	82,000	●
4,400		126,000	82,000	●