


Артикул №	8924
Стандарт	DIN 345
Режущий материал	HSS
Покрытие	●
Тип	N
Направление резания	правое
Допуск	h8
Группа скидок	101

Диапазон диаметров: 9,000 - 40,000

Затыловка: Конусная

Угол при вершине сверла: 118°

Подточка ≥Ø: 14,01 мм



d1 мм	d1 дюйм	MK	l1 мм	l2 мм	Наличие на складе
9,000		1	162,000	81,000	●
9,500		1	162,000	81,000	●
10,000		1	168,000	87,000	●
10,200		1	168,000	87,000	●
10,500		1	168,000	87,000	●
11,000		1	175,000	94,000	●
11,500		1	175,000	94,000	●
12,000		1	182,000	101,000	●
12,500		1	182,000	101,000	●
12,700	1/2	1	182,000	101,000	●
13,000		1	182,000	101,000	●
13,500		1	189,000	108,000	●
14,000		1	189,000	108,000	●
14,500		2	212,000	114,000	●
15,000		2	212,000	114,000	●
15,500		2	218,000	120,000	●
15,870	5/8	2	218,000	120,000	●
16,000		2	218,000	120,000	●
16,500		2	223,000	125,000	●
17,000		2	223,000	125,000	●
17,500		2	228,000	130,000	●
18,000		2	228,000	130,000	●
18,500		2	233,000	135,000	●
19,000		2	233,000	135,000	●
19,050	3/4	2	238,000	140,000	●
19,500		2	238,000	140,000	●
20,000		2	238,000	140,000	●
20,500		2	243,000	145,000	●
21,000		2	243,000	145,000	●
21,500		2	248,000	150,000	●
22,000		2	248,000	150,000	●
22,500		2	253,000	155,000	●
23,000		2	253,000	155,000	●
23,500		3	276,000	155,000	●
24,000		3	281,000	160,000	●
24,500		3	281,000	160,000	●
25,000	63/64	3	281,000	160,000	●
25,400	1	3	286,000	165,000	●
25,500		3	286,000	165,000	●

● обработка паром