

DRILLS

GUHRING

GUHRING Select Series # 205 (DVHS) HSS general purpose (Type N), jobber length, 118° point, standard straight shank, steam oxide

GUHRING Select Series # 205 (DVHS) HSS general purpose (Type N), jobber length, 118° point, standard straight shank, steam oxide

EDP Number	Diameter				Pkg. Qty.	List Price	
	mm	decimal inch	fraction inch	wire/letter		per piece	
9002050062000	6.200	0.2441			10	6.10	
9002050062200	6.220	0.2449			10	12.62	
9002050062500	6.250	0.2461		D	10	6.39	
9002050063000	6.300	0.2480			10	6.10	
9002050063500	6.350	0.2500	1/4	E	10	5.28	
9002050064000	6.400	0.2520			10	6.10	
9002050064500	6.450	0.2539			10	11.13	
9002050065000	6.500	0.2559			10	6.10	
9002050065300	6.530	0.2571		F	10	6.81	
9002050065500	6.550	0.2579			10	11.70	
9002050066000	6.600	0.2598			10	6.60	
9002050066300	6.630	0.2610		G	10	7.64	
9002050066500	6.650	0.2618			10	11.70	
9002050067000	6.700	0.2638			10	7.40	
9002050067500	6.750	0.2657	17/64	H	10	6.44	
9002050067600	6.760	0.2661			10	12.62	
9002050068000	6.800	0.2677			10	7.70	
9002050068500	6.850	0.2697			10	12.62	
9002050069000	6.900	0.2717		I	10	7.64	
9002050069500	6.950	0.2736			10	12.62	
9002050070000	7.000	0.2756			10	6.90	
9002050070300	7.030	0.2768		J	10	8.21	
9002050070500	7.050	0.2776			10	13.42	
9002050071000	7.100	0.2795			10	8.90	
9002050071400	7.140	0.2811	9/32	K	10	6.61	
9002050071500	7.150	0.2815			10	13.42	
9002050072000	7.200	0.2835			10	8.90	
9002050072500	7.250	0.2854			10	12.65	
9002050073000	7.300	0.2874			10	8.90	
9002050073500	7.350	0.2894			10	13.42	
9002050073700	7.370	0.2902		L	10	9.07	
9002050074000	7.400	0.2913			10	8.65	
9002050074500	7.450	0.2933			10	13.42	
9002050074900	7.490	0.2949		M	10	9.61	
9002050075000	7.500	0.2953			10	7.90	
9002050075400	7.540	0.2969	19/64		5	7.68	
9002050075500	7.550	0.2972			5	15.75	
9002050076000	7.600	0.2992			5	9.29	
9002050076500	7.650	0.3012			5	15.75	
9002050076700	7.670	0.3020		N	5	9.61	
9002050077000	7.700	0.3031			5	9.29	
9002050077500	7.750	0.3051			5	14.06	
9002050078000	7.800	0.3071			5	9.20	
9002050078500	7.850	0.3091			5	15.75	
9002050079000	7.900	0.3110			5	9.20	
9002050079400	7.940	0.3126	5/16		5	8.48	
9002050079500	7.950	0.3130			5	16.67	
9002050079800	7.980	0.3142			5	16.67	
9002050080000	8.000	0.3150			5	7.80	
9002050080300	8.030	0.3161		O	5	9.71	
9002050080500	8.050	0.3169			5	16.67	
9002050081000	8.100	0.3189			5	9.29	
9002050081300	8.130	0.3201			5	24.70	
9002050081500	8.150	0.3209			5	16.67	
9002050082000	8.200	0.3228		P	5	10.97	
9002050082500	8.250	0.3248			5	11.70	
9002050083000	8.300	0.3268			5	11.70	
9002050083300	8.330	0.3280	21/64		5	9.44	
9002050083500	8.350	0.3287			5	18.24	
9002050084000	8.400	0.3307			5	11.10	
9002050084300	8.430	0.3319		Q	5	10.91	
9002050084500	8.450	0.3327			5	19.16	
9002050085000	8.500	0.3346			5	10.00	

EDP Number	Diameter				Pkg. Qty.	List Price	
	mm	decimal inch	fraction inch	wire/letter		per piece	
9002050085500	8.550	0.3366			5	21.42	
9002050086000	8.600	0.3386			5	11.70	
9002050086100	8.610	0.3390		R	5	11.73	
9002050086500	8.650	0.3406			5	22.34	
9002050087000	8.700	0.3425			5	11.70	
9002050087300	8.730	0.3437	11/32		5	10.51	
9002050087500	8.750	0.3445			5	19.93	
9002050088000	8.800	0.3465			5	12.60	
9002050088400	8.840	0.3480		S	5	12.42	
9002050088500	8.850	0.3484			5	22.34	
9002050089000	8.900	0.3504			5	12.60	
9002050089500	8.950	0.3524			5	23.14	
9002050090000	9.000	0.3543			5	11.20	
9002050090500	9.050	0.3563			5	23.93	
9002050090900	9.090	0.3579		T	5	14.15	
9002050091000	9.100	0.3583			5	12.70	
9002050091300	9.130	0.3594	23/64		5	11.79	
9002050091500	9.150	0.3602			5	23.93	
9002050092000	9.200	0.3622			5	12.70	
9002050092500	9.250	0.3642			5	17.44	
9002050093000	9.300	0.3661			5	12.70	
9002050093400	9.340	0.3677		U	5	14.15	
9002050093500	9.350	0.3681			5	23.93	
9002050094000	9.400	0.3701			5	12.70	
9002050094500	9.450	0.3720			5	23.93	
9002050095000	9.500	0.3740			5	12.70	
9002050095200	9.520	0.3748	3/8		5	12.08	
9002050095500	9.550	0.3760			5	28.76	
9002050095800	9.580	0.3772		V	5	14.49	
9002050096000	9.600	0.3780			5	14.10	
9002050096500	9.650	0.3799			5	28.76	
9002050097000	9.700	0.3819			5	14.10	
9002050097500	9.750	0.3839			5	19.16	
9002050098000	9.800	0.3858		W	5	15.01	
9002050098500	9.850	0.3878			5	30.40	
9002050099000	9.900	0.3898			5	15.75	
9002050099200	9.920	0.3906	25/64		5	13.86	
9002050099500	9.950	0.3917			5	30.40	
9002050100000	10.000	0.3937			5	13.86	
9002050100400	10.040	0.3953			5	38.45	
9002050100800	10.080	0.3969		X	5	18.23	
9002050101000	10.100	0.3976			5	16.67	
9002050101500	10.150	0.3996			5	40.33	
9002050102000	10.200	0.4016			5	16.80	
9002050102500	10.250	0.4035			5	22.34	
9002050102600	10.260	0.4039		Y	5	20.41	
9002050103000	10.300	0.4055			5	20.52	
9002050103200	10.320	0.4063	13/32		5	14.20	
9002050103500	10.350	0.4075			5	40.33	
9002050104000	10.400	0.4094			5	19.93	
9002050104900	10.490	0.4130		Z	5	21.74	
9002050105000	10.500	0.4134			5	16.80	
9002050106000	10.600	0.4173			5	21.42	
9002050107000	10.700	0.4213			1	24.70	
9002050107200	10.720	0.4220	27/64		1	15.87	
9002050107500	10.750	0.4232			1	27.17	
9002050108000	10.800	0.4252			1	24.00	
9002050109000	10.900	0.4291			1	25.63	
9002050110000	11.000	0.4331			1	18.94	
9002050110500	11.050	0.4350			1	93.40	
9002050111000	11.100	0.4370			1	25.63	
9002050111100	11.110	0.4374	7/16		1	16.39	
9002050111500	11.150	0.4390			1	47.56	

DRILLING