

DRILLS

GUHRING

Series # 206 (D)

HSS Low Helix (Type H), jobber length, 118° point, standard straight shank, bright

EDP Number	Diameter				Pkg. Qty.	List Price per piece
	mm	decimal inch	fraction inch	wire/letter		
9002060002000	0.200	0.0079		92	10	10.73
9002060002400	0.240	0.0094		88	10	13.37
9002060002500	0.250	0.0098		87	10	9.31
9002060003000	0.300	0.0118			10	9.31
9002060003400	0.340	0.0134		80	10	13.37
9002060003500	0.350	0.0138			10	6.63
9002060004000	0.400	0.0157	1/64		10	6.63
9002060004100	0.410	0.0161		78	10	10.73
9002060004500	0.450	0.0177			10	6.63
9002060004600	0.460	0.0181		77	10	9.31
9002060005000	0.500	0.0197			10	4.64
9002060005100	0.510	0.0201		76	10	7.27
9002060005300	0.530	0.0209		75	10	6.63
9002060005500	0.550	0.0217			10	6.63
9002060005700	0.570	0.0224		74	10	6.63
9002060006000	0.600	0.0236			10	4.64
9002060006200	0.620	0.0244			10	6.63
9002060006500	0.650	0.0256			10	6.63
9002060006600	0.660	0.0260		71	10	6.63
9002060007000	0.700	0.0276			10	4.64
9002060007200	0.720	0.0283			10	7.27
9002060007300	0.730	0.0287			10	5.59
9002060007400	0.740	0.0291		69	10	5.59
9002060007500	0.750	0.0295			10	5.08
9002060007600	0.760	0.0299			10	5.59
9002060007700	0.770	0.0303			10	5.59
9002060007900	0.790	0.0311	1/32	68	10	3.16
9002060008000	0.800	0.0315			10	4.11
9002060008100	0.810	0.0319		67	10	5.26
9002060008300	0.830	0.0327			10	5.59
9002060008400	0.840	0.0331		66	10	5.02
9002060008500	0.850	0.0335			10	4.77
9002060008600	0.860	0.0339			10	6.63
9002060008700	0.870	0.0343			10	6.63
9002060008800	0.880	0.0346			10	5.26
9002060008900	0.890	0.0350		65	10	5.91
9002060009000	0.900	0.0354			10	4.05
9002060009100	0.910	0.0358		64	10	5.26
9002060009300	0.930	0.0366			10	6.63
9002060009500	0.950	0.0374			10	4.69
9002060009600	0.960	0.0378			10	6.63
9002060009700	0.970	0.0382		62	10	5.26
9002060009900	0.990	0.0390		61	10	5.26
9002060010000	1.000	0.0394			10	3.55
9002060010200	1.020	0.0402		60	10	4.82
9002060010400	1.040	0.0409		59	10	6.63
9002060010500	1.050	0.0413			10	4.64
9002060011000	1.100	0.0433			10	3.67
9002060011500	1.150	0.0453			10	4.11
9002060011800	1.180	0.0465		56	10	6.63
9002060011900	1.190	0.0469	3/64		10	3.67
9002060012000	1.200	0.0472			10	3.67
9002060012200	1.220	0.0480			10	6.63
9002060012500	1.250	0.0492			10	4.11
9002060012700	1.270	0.0500			10	6.63
9002060012800	1.280	0.0504			10	4.57
9002060013000	1.300	0.0512			10	3.67
9002060013200	1.320	0.0520		55	10	4.77
9002060013300	1.330	0.0524			10	4.88
9002060013500	1.350	0.0531			10	4.18
9002060013700	1.370	0.0539			10	4.88
9002060014000	1.400	0.0551		54	10	3.16
9002060014300	1.430	0.0563			10	5.41

Series # 206 (D)

HSS Low Helix (Type H), jobber length, 118° point, standard straight shank, bright

EDP Number	Diameter				Pkg. Qty.	List Price per piece
	mm	decimal inch	fraction inch	wire/letter		
9002060014400	1.440	0.0567			10	5.91
9002060014500	1.450	0.0571			10	4.11
9002060014700	1.470	0.0579			10	5.91
9002060015000	1.500	0.0591			10	3.46
9002060015300	1.530	0.0602			10	5.91
9002060015400	1.540	0.0606			10	5.21
9002060015500	1.550	0.0610			10	4.11
9002060015900	1.590	0.0626	1/16		10	3.16
9002060016000	1.600	0.0630			10	3.22
9002060016200	1.620	0.0638			10	5.91
9002060016500	1.650	0.0650			10	4.11
9002060016700	1.670	0.0657			10	6.12
9002060017000	1.700	0.0669		51	10	3.16
9002060017200	1.720	0.0677			10	3.78
9002060017300	1.730	0.0681			10	5.91
9002060017500	1.750	0.0689			10	4.11
9002060017800	1.780	0.0701		50	10	3.78
9002060018000	1.800	0.0709			10	3.46
9002060018500	1.850	0.0728		49	10	3.16
9002060019000	1.900	0.0748			10	3.22
9002060019200	1.920	0.0756			10	5.91
9002060019500	1.950	0.0768			10	3.78
9002060019800	1.980	0.0780	5/64		10	3.16
9002060020000	2.000	0.0787			10	2.90
9002060020200	2.020	0.0795			10	5.02
9002060020500	2.050	0.0807			10	3.78
9002060020600	2.060	0.0811		46	10	4.44
9002060020700	2.070	0.0815			10	4.44
9002060021000	2.100	0.0827			10	3.16
9002060021500	2.150	0.0846			10	3.78
9002060021800	2.180	0.0858		44	10	3.73
9002060022000	2.200	0.0866			10	3.28
9002060022500	2.250	0.0886			10	3.78
9002060022700	2.270	0.0894			10	5.91
9002060023000	2.300	0.0906			10	3.16
9002060023500	2.350	0.0925			10	4.11
9002060023800	2.380	0.0937	3/32		10	3.16
9002060024000	2.400	0.0945			10	3.28
9002060024500	2.450	0.0965			10	4.18
9002060024700	2.470	0.0972			10	5.36
9002060025000	2.500	0.0984			10	3.16
9002060025300	2.530	0.0996		39	10	5.59
9002060025500	2.550	0.1004			10	4.18
9002060025700	2.570	0.1012			10	5.91
9002060026000	2.600	0.1024			10	3.55
9002060026300	2.630	0.1035			10	5.91
9002060026400	2.640	0.1039		37	10	5.02
9002060026500	2.650	0.1043			10	4.18
9002060027000	2.700	0.1063			10	3.55
9002060027100	2.710	0.1067		36	10	3.93
9002060027500	2.750	0.1083			10	4.44
9002060027800	2.780	0.1094	7/64		10	3.16
9002060028000	2.800	0.1102			10	3.55
9002060028200	2.820	0.1110		34	10	5.02
9002060028500	2.850	0.1122			10	5.02
9002060029000	2.900	0.1142			10	3.55
9002060029200	2.920	0.1150			10	4.44
9002060029500	2.950	0.1161		32	10	3.16
9002060030000	3.000	0.1181			10	3.16
9002060030500	3.050	0.1201		31	10	3.16
9002060031000	3.100	0.1220			10	4.00
9002060031500	3.150	0.1240			10	4.82
9002060031700	3.170	0.1248	1/8		10	3.16

DRILLING