

GUHRING

DRILLS

Series # 208 (D)

HSS general purpose (Type N), jobber length, 118° point, standard straight shank, steam oxide, LH

EDP Number	Diameter				List Price	
	mm	decimal inch	fraction inch	wire/letter	Pkg. Qty.	per piece
9002080002400	0.240	0.0094		88	10	22.39
9002080002900	0.290	0.0114		84	10	16.60
9002080003000	0.300	0.0118			10	11.60
9002080003400	0.340	0.0134		80	10	16.09
9002080003500	0.350	0.0138			10	11.60
9002080003600	0.360	0.0142			10	16.09
9002080003700	0.370	0.0146		79	10	16.09
9002080004000	0.400	0.0157	1/64		10	5.26
9002080004100	0.410	0.0161		78	10	15.94
9002080004200	0.420	0.0165			10	15.94
9002080004300	0.430	0.0169			10	15.94
9002080004400	0.440	0.0173			10	15.94
9002080004500	0.450	0.0177			10	5.91
9002080004600	0.460	0.0181		77	10	15.32
9002080004700	0.470	0.0185			10	15.32
9002080004800	0.480	0.0189			10	15.32
9002080005000	0.500	0.0197			10	3.93
9002080005100	0.510	0.0201		76	10	14.54
9002080005200	0.520	0.0205			10	14.54
9002080005300	0.530	0.0209		75	10	14.54
9002080005400	0.540	0.0213			10	5.02
9002080005500	0.550	0.0217			10	4.64
9002080005600	0.560	0.0220			10	8.31
9002080005700	0.570	0.0224		74	10	8.31
9002080005800	0.580	0.0228			10	8.31
9002080006000	0.600	0.0236			10	3.93
9002080006100	0.610	0.0240		73	10	8.31
9002080006200	0.620	0.0244			10	8.31
9002080006300	0.630	0.0248			10	8.31
9002080006400	0.640	0.0252		72	10	8.31
9002080006500	0.650	0.0256			10	4.64
9002080006600	0.660	0.0260		71	10	8.31
9002080006700	0.670	0.0264			10	6.63
9002080006800	0.680	0.0268			10	6.63
9002080007000	0.700	0.0276			10	3.93
9002080007100	0.710	0.0280		70	10	6.63
9002080007200	0.720	0.0283			10	6.63
9002080007300	0.730	0.0287			10	5.79
9002080007500	0.750	0.0295			10	3.93
9002080007700	0.770	0.0303			10	5.91
9002080007800	0.780	0.0307			10	5.91
9002080007900	0.790	0.0311	1/32	68	10	3.35
9002080008000	0.800	0.0315			10	3.22
9002080008100	0.810	0.0319		67	10	5.91
9002080008200	0.820	0.0323			10	5.91
9002080008300	0.830	0.0327			10	5.91
9002080008400	0.840	0.0331		66	10	5.91
9002080008500	0.850	0.0335			10	3.35
9002080008600	0.860	0.0339			10	5.91
9002080008700	0.870	0.0343			10	5.91
9002080008800	0.880	0.0346			10	5.91
9002080008900	0.890	0.0350		65	10	5.91
9002080009000	0.900	0.0354			10	3.35
9002080009100	0.910	0.0358		64	10	5.91
9002080009200	0.920	0.0362			10	5.91
9002080009300	0.930	0.0366			10	5.91
9002080009500	0.950	0.0374			10	3.35
9002080009600	0.960	0.0378			10	5.91
9002080009700	0.970	0.0382		62	10	5.26
9002080009800	0.980	0.0386			10	5.47
9002080009900	0.990	0.0390		61	10	5.47
9002080010000	1.000	0.0394			10	2.52
9002080010200	1.020	0.0402		60	10	5.47

Series # 208 (D)

HSS general purpose (Type N), jobber length, 118° point, standard straight shank, steam oxide, LH

EDP Number	Diameter				List Price	
	mm	decimal inch	fraction inch	wire/letter	Pkg. Qty.	per piece
9002080010400	1.040	0.0409		59	10	5.47
9002080010500	1.050	0.0413			10	3.01
9002080010700	1.070	0.0421		58	10	5.26
9002080010800	1.080	0.0425			10	5.26
9002080010900	1.090	0.0429		57	10	5.26
9002080011000	1.100	0.0433			10	3.01
9002080011200	1.120	0.0441			10	5.26
9002080011300	1.130	0.0445			10	5.26
9002080011500	1.150	0.0453			10	3.01
9002080011700	1.170	0.0461			10	4.82
9002080011800	1.180	0.0465		56	10	2.78
9002080011900	1.190	0.0469	3/64		10	2.78
9002080012000	1.200	0.0472			10	2.78
9002080012100	1.210	0.0476			10	4.82
9002080012200	1.220	0.0480			10	4.82
9002080012400	1.240	0.0488			10	4.82
9002080012500	1.250	0.0492			10	2.78
9002080012700	1.270	0.0500			10	4.82
9002080013000	1.300	0.0512			10	2.78
9002080013200	1.320	0.0520		55	10	4.64
9002080013500	1.350	0.0531			10	2.78
9002080013800	1.380	0.0543			10	4.64
9002080013900	1.390	0.0547			10	4.64
9002080014000	1.400	0.0551		54	10	2.52
9002080014200	1.420	0.0559			10	4.64
9002080014500	1.450	0.0571			10	2.78
9002080014700	1.470	0.0579			10	4.64
9002080015000	1.500	0.0591			10	2.37
9002080015100	1.510	0.0594		53	10	3.93
9002080015300	1.530	0.0602			10	3.93
9002080015500	1.550	0.0610			10	2.52
9002080015600	1.560	0.0614			10	3.93
9002080015900	1.590	0.0626	1/16		10	2.37
9002080016000	1.600	0.0630			10	2.37
9002080016100	1.610	0.0634		52	10	3.93
9002080016200	1.620	0.0638			10	3.93
9002080016300	1.630	0.0642			10	3.93
9002080016500	1.650	0.0650			10	2.37
9002080016600	1.660	0.0654			10	3.93
9002080016800	1.680	0.0661			10	3.93
9002080017000	1.700	0.0669		51	10	2.37
9002080017200	1.720	0.0677			10	3.93
9002080017300	1.730	0.0681			10	3.93
9002080017500	1.750	0.0689			10	2.37
9002080017600	1.760	0.0693			10	3.93
9002080018000	1.800	0.0709			10	2.37
9002080018200	1.820	0.0717			10	3.93
9002080018300	1.830	0.0720			10	3.93
9002080018400	1.840	0.0724			10	2.45
9002080018500	1.850	0.0728		49	10	2.37
9002080019000	1.900	0.0748			10	2.37
9002080019300	1.930	0.0760		48	10	3.93
9002080019400	1.940	0.0764			10	3.93
9002080019500	1.950	0.0768			10	2.37
9002080019700	1.970	0.0776			10	3.93
9002080019800	1.980	0.0780	5/64		10	2.37
9002080020000	2.000	0.0787			10	2.37
9002080020400	2.040	0.0803			10	3.93
9002080020500	2.050	0.0807			10	2.37
9002080020600	2.060	0.0811		46	10	3.46
9002080020800	2.080	0.0819		45	10	3.46
9002080021000	2.100	0.0827			10	2.37
9002080021200	2.120	0.0835			10	3.93