

GUHRING

DRILLS

Series # 225 (D)

HSS High Helix (Type W), stub length, 130° point, standard straight shank, bright

EDP Number	Diameter				List Price	
	mm	decimal inch	fraction inch	wire/letter	Pkg. Qty.	per piece
9002250127000	12.700	0.5000	1/2		1	34.99
9002250128000	12.800	0.5039			1	51.27
9002250130000	13.000	0.5118			1	35.71
9002250140000	14.000	0.5512			1	35.71
9002250145000	14.500	0.5709			1	91.23
9002250150000	15.000	0.5906			1	49.61
9002250160000	16.000	0.6299			1	57.98
9002250170000	17.000	0.6693			1	105.39
9002250175000	17.500	0.6890			1	175.62
9002250180000	18.000	0.7087			1	105.39
9002250190000	19.000	0.7480			1	135.12
9002250200000	20.000	0.7874			1	168.88

Series # 226 (D)

HSS general purpose (Type N), stub length, 118° point, standard straight shank, steam oxide, LH

EDP Number	Diameter				List Price	
	mm	decimal inch	fraction inch	wire/letter	Pkg. Qty.	per piece
9002260005000	0.500	0.0197			10	6.12
9002260005500	0.550	0.0217			10	8.87
9002260006000	0.600	0.0236			10	5.79
9002260006500	0.650	0.0256			10	7.27
9002260007000	0.700	0.0276			10	5.54
9002260007500	0.750	0.0295			10	5.91
9002260008000	0.800	0.0315			10	4.64
9002260008500	0.850	0.0335			10	5.54
9002260009000	0.900	0.0354			10	4.18
9002260009500	0.950	0.0374			10	4.82
9002260010000	1.000	0.0394			10	2.78
9002260010200	1.020	0.0402		60	10	4.82
9002260010500	1.050	0.0413			10	4.82
9002260010700	1.070	0.0421		58	10	4.82
9002260010900	1.090	0.0429		57	10	4.82
9002260011000	1.100	0.0433			10	3.22
9002260011500	1.150	0.0453			10	4.26
9002260011800	1.180	0.0465		56	10	4.26
9002260011900	1.190	0.0469	3/64		10	3.08
9002260012000	1.200	0.0472			10	3.08
9002260012500	1.250	0.0492			10	4.26
9002260013000	1.300	0.0512			10	3.08
9002260013200	1.320	0.0520		55	10	4.11
9002260013300	1.330	0.0524			10	4.96
9002260013500	1.350	0.0531			10	4.11
9002260014000	1.400	0.0551		54	10	3.08
9002260014500	1.450	0.0571			10	4.11
9002260015000	1.500	0.0591			10	3.08
9002260015100	1.510	0.0594		53	10	4.11
9002260015500	1.550	0.0610			10	3.93
9002260015900	1.590	0.0626	1/16		10	3.08
9002260016000	1.600	0.0630			10	3.08
9002260016100	1.610	0.0634		52	10	4.11
9002260016500	1.650	0.0650			10	3.93
9002260017000	1.700	0.0669		51	10	3.08
9002260017500	1.750	0.0689			10	3.87
9002260017800	1.780	0.0701		50	10	4.11
9002260018000	1.800	0.0709			10	3.08
9002260018100	1.810	0.0713			10	4.11
9002260018500	1.850	0.0728		49	10	4.11
9002260019000	1.900	0.0748			10	3.08
9002260019300	1.930	0.0760		48	10	3.73
9002260019500	1.950	0.0768			10	3.73

Series # 226 (D)

HSS general purpose (Type N), stub length, 118° point, standard straight shank, steam oxide, LH

EDP Number	Diameter				List Price	
	mm	decimal inch	fraction inch	wire/letter	Pkg. Qty.	per piece
9002260019900	1.990	0.0783		47	10	3.73
9002260020000	2.000	0.0787			10	2.45
9002260020500	2.050	0.0807			10	3.73
9002260020600	2.060	0.0811		46	10	3.73
9002260020800	2.080	0.0819		45	10	3.73
9002260021000	2.100	0.0827			10	2.45
9002260021500	2.150	0.0846			10	3.73
9002260021800	2.180	0.0858		44	10	3.73
9002260022000	2.200	0.0866			10	2.52
9002260022500	2.250	0.0886			10	4.57
9002260022600	2.260	0.0890		43	10	3.73
9002260023000	2.300	0.0906			10	2.52
9002260023500	2.350	0.0925			10	4.57
9002260023700	2.370	0.0933		42	10	5.47
9002260023800	2.380	0.0937	3/32		10	2.25
9002260024000	2.400	0.0945			10	2.78
9002260024400	2.440	0.0961		41	10	4.38
9002260024500	2.450	0.0965			10	5.54
9002260024900	2.490	0.0980		40	10	5.54
9002260025000	2.500	0.0984			10	2.25
9002260025300	2.530	0.0996		39	10	5.54
9002260025500	2.550	0.1004			10	5.54
9002260025800	2.580	0.1016		38	10	5.54
9002260026000	2.600	0.1024			10	2.78
9002260026400	2.640	0.1039		37	10	5.54
9002260026500	2.650	0.1043			10	5.86
9002260027000	2.700	0.1063			10	2.78
9002260027100	2.710	0.1067		36	10	5.54
9002260027500	2.750	0.1083			10	5.54
9002260027800	2.780	0.1094	7/64		10	2.78
9002260027900	2.790	0.1098		35	10	5.79
9002260028000	2.800	0.1102			10	3.01
9002260028200	2.820	0.1110		34	10	5.79
9002260028500	2.850	0.1122			10	6.36
9002260028700	2.870	0.1130		33	10	5.79
9002260029000	2.900	0.1142			10	3.01
9002260029500	2.950	0.1161		32	10	5.79
9002260030000	3.000	0.1181			10	2.45
9002260030500	3.050	0.1201		31	10	5.79
9002260031000	3.100	0.1220			10	3.08
9002260031500	3.150	0.1240			10	6.36
9002260031700	3.170	0.1248	1/8		10	2.25
9002260032000	3.200	0.1260			10	3.08
9002260032300	3.230	0.1272			10	6.36
9002260032500	3.250	0.1280			10	6.36
9002260032600	3.260	0.1283		30	10	5.79
9002260033000	3.300	0.1299			10	3.08
9002260033500	3.350	0.1319			10	6.36
9002260034000	3.400	0.1339			10	3.55
9002260034500	3.450	0.1358		29	10	6.36
9002260035000	3.500	0.1378			10	3.01
9002260035500	3.550	0.1398			10	6.36
9002260036000	3.600	0.1417			10	3.55
9002260037000	3.700	0.1457			10	3.55
9002260037300	3.730	0.1469		26	10	6.50
9002260037500	3.750	0.1476			10	6.63
9002260037700	3.770	0.1484			10	9.97
9002260038000	3.800	0.1496		25	10	3.55
9002260038400	3.840	0.1512			10	7.45
9002260038500	3.850	0.1516			10	7.45
9002260038600	3.860	0.1520		24	10	7.45
9002260039000	3.900	0.1535			10	3.60
9002260039100	3.910	0.1539		23	10	7.45