

## DRILLS

## GUHRING

## Series # 226 (D)

HSS general purpose (Type N), stub length, 118° point,  
standard straight shank, steam oxide, LH

EDP Number	Diameter				List Price	
	mm	decimal inch	fraction inch	wire/ letter	Pkg. Qty.	per piece
9002260039500	3.950	0.1555			10	7.45
9002260039700	3.970	0.1563	5/32		10	2.78
9002260039900	3.990	0.1571		22	10	3.01
9002260040000	4.000	0.1575			10	3.55
9002260040400	4.040	0.1591		21	10	7.45
9002260040500	4.050	0.1594			10	7.45
9002260041000	4.100	0.1614			10	3.55
9002260041500	4.150	0.1634			10	7.45
9002260042000	4.200	0.1654			10	3.55
9002260042200	4.220	0.1661		19	10	7.45
9002260042500	4.250	0.1673			10	8.22
9002260043000	4.300	0.1693		18	10	4.26
9002260043500	4.350	0.1713			10	9.31
9002260043700	4.370	0.1720	11/64		10	4.26
9002260043900	4.390	0.1728		17	10	9.31
9002260044000	4.400	0.1732			10	4.26
9002260044500	4.450	0.1752			10	9.31
9002260045000	4.500	0.1772		16	10	3.55
9002260045700	4.570	0.1799		15	10	9.31
9002260046000	4.600	0.1811			10	4.26
9002260047000	4.700	0.1850		13	10	4.26
9002260047500	4.750	0.1870			10	9.31
9002260047600	4.760	0.1874	3/16		10	3.55
9002260048000	4.800	0.1890		12	10	4.38
9002260048500	4.850	0.1909		11	10	7.60
9002260049000	4.900	0.1929			10	4.38
9002260049200	4.920	0.1937		10	10	9.31
9002260049800	4.980	0.1961		9	10	9.31
9002260050000	5.000	0.1969			10	4.38
9002260050500	5.050	0.1988			10	9.31
9002260051000	5.100	0.2008			10	4.38
9002260051100	5.110	0.2012		7	10	9.31
9002260051500	5.150	0.2028			10	9.59
9002260051600	5.160	0.2031	13/64		10	4.38
9002260051800	5.180	0.2039		6	10	9.59
9002260052000	5.200	0.2047			10	4.82
9002260052200	5.220	0.2055		5	10	9.59
9002260052500	5.250	0.2067			10	9.59
9002260053000	5.300	0.2087			10	4.82
9002260053100	5.310	0.2091		4	10	10.73
9002260053500	5.350	0.2106			10	11.98
9002260054000	5.400	0.2126			10	5.02
9002260054100	5.410	0.2130		3	10	10.73
9002260055000	5.500	0.2165			10	5.02
9002260055600	5.560	0.2189	7/32		10	5.02
9002260056000	5.600	0.2205			10	5.02
9002260056100	5.610	0.2209		2	10	10.73
9002260056500	5.650	0.2224			10	10.73
9002260057000	5.700	0.2244			10	5.02
9002260057500	5.750	0.2264			10	10.73
9002260057900	5.790	0.2280		1	10	10.73
9002260058000	5.800	0.2283			10	5.02
9002260059000	5.900	0.2323			10	5.02
9002260059500	5.950	0.2343	15/64		10	10.73
9002260060000	6.000	0.2362			10	5.02
9002260060400	6.040	0.2378		B	10	12.67
9002260061000	6.100	0.2402			10	5.02
9002260061500	6.150	0.2421		C	10	13.25
9002260062000	6.200	0.2441			10	5.02
9002260062500	6.250	0.2461		D	10	13.25
9002260063000	6.300	0.2480			10	5.02
9002260063500	6.350	0.2500	1/4	E	10	10.73
9002260064000	6.400	0.2520			10	5.02

## Series # 226 (D)

HSS general purpose (Type N), stub length, 118° point,  
standard straight shank, steam oxide, LH

EDP Number	Diameter				List Price	
	mm	decimal inch	fraction inch	wire/ letter	Pkg. Qty.	per piece
9002260065000	6.500	0.2559			10	5.02
9002260065300	6.530	0.2571		F	10	13.25
9002260066000	6.600	0.2598			10	5.66
9002260066300	6.630	0.2610		G	10	13.25
9002260067000	6.700	0.2638			10	5.66
9002260067500	6.750	0.2657	17/64	H	10	11.98
9002260068000	6.800	0.2677			10	6.36
9002260069000	6.900	0.2717		I	10	6.36
9002260069500	6.950	0.2736			10	15.44
9002260070000	7.000	0.2756			10	6.36
9002260071000	7.100	0.2795			10	7.01
9002260071400	7.140	0.2811	9/32	K	10	13.37
9002260072000	7.200	0.2835			10	8.69
9002260072500	7.250	0.2854			10	16.81
9002260073000	7.300	0.2874			10	8.69
9002260073700	7.370	0.2902		L	10	16.81
9002260074000	7.400	0.2913			10	8.69
9002260074900	7.490	0.2949		M	10	16.81
9002260075000	7.500	0.2953			10	6.63
9002260075400	7.540	0.2969	19/64		5	8.69
9002260076000	7.600	0.2992			5	8.69
9002260077000	7.700	0.3031			5	8.69
9002260077500	7.750	0.3051			5	18.77
9002260078000	7.800	0.3071			5	8.69
9002260079000	7.900	0.3110			5	8.69
9002260079400	7.940	0.3126	5/16		5	8.69
9002260080000	8.000	0.3150			5	7.27
9002260080300	8.030	0.3161		O	5	18.77
9002260081000	8.100	0.3189			5	9.59
9002260082000	8.200	0.3228		P	5	9.59
9002260083000	8.300	0.3268			5	9.59
9002260084000	8.400	0.3307			5	9.59
9002260084300	8.430	0.3319		Q	5	18.77
9002260085000	8.500	0.3346			5	7.99
9002260086000	8.600	0.3386			5	10.18
9002260087000	8.700	0.3425			5	10.18
9002260087300	8.730	0.3437	11/32		5	10.18
9002260087500	8.750	0.3445			5	21.49
9002260088000	8.800	0.3465			5	10.88
9002260088400	8.840	0.3480		S	5	21.49
9002260089000	8.900	0.3504			5	10.88
9002260090000	9.000	0.3543			5	9.31
9002260090900	9.090	0.3579		T	5	21.49
9002260091000	9.100	0.3583			5	12.67
9002260091300	9.130	0.3594	23/64		5	12.67
9002260092000	9.200	0.3622			5	12.67
9002260093400	9.340	0.3677		U	5	23.54
9002260094000	9.400	0.3701			5	13.37
9002260095000	9.500	0.3740			5	11.39
9002260095200	9.520	0.3748	3/8		5	14.67
9002260096000	9.600	0.3780			5	14.67
9002260097000	9.700	0.3819			5	14.67
9002260097500	9.750	0.3839			5	23.54
9002260098000	9.800	0.3858		W	5	15.44
9002260099000	9.900	0.3898			5	15.44
9002260100000	10.000	0.3937			5	11.39
9002260100800	10.080	0.3969		X	5	19.44
9002260101000	10.100	0.3976			5	19.44
9002260102000	10.200	0.4016			5	19.44
9002260102500	10.250	0.4035			5	19.44
9002260103000	10.300	0.4055			5	19.44
9002260103200	10.320	0.4063	13/32		5	14.08
9002260104000	10.400	0.4094			5	19.44

DRILLING