

DRILLS

GUHRING

Series # 235 (D)

HSS general purpose (Type N), extra length #1, 118° point, standard straight shank, steam oxide

EDP Number	Diameter				List Price	
	mm	decimal inch	fraction inch	wire/ letter	Pkg. Qty.	per piece
9002350080000	8.000	0.3150			5	23.54
9002350081000	8.100	0.3189			5	30.30
9002350082000	8.200	0.3228		P	5	30.30
9002350083000	8.300	0.3268			5	30.30
9002350083300	8.330	0.3280	21/64		5	23.54
9002350084000	8.400	0.3307			5	30.30
9002350085000	8.500	0.3346			5	26.26
9002350086000	8.600	0.3386			5	33.00
9002350087000	8.700	0.3425			5	33.00
9002350087300	8.730	0.3437	11/32		5	33.00
9002350088000	8.800	0.3465			5	33.00
9002350090000	9.000	0.3543			5	28.95
9002350091300	9.130	0.3594	23/64		5	37.71
9002350095000	9.500	0.3740			5	33.00
9002350095200	9.520	0.3748	3/8		5	33.00
9002350096000	9.600	0.3780			5	39.75
9002350097000	9.700	0.3819			5	39.75
9002350098000	9.800	0.3858		W	5	39.75
9002350099000	9.900	0.3898			5	43.80
9002350100000	10.000	0.3937			5	43.80
9002350103200	10.320	0.4063	13/32		5	43.80
9002350105000	10.500	0.4134			5	43.80
9002350110000	11.000	0.4331			1	53.34
9002350111100	11.110	0.4374	7/16		1	53.34
9002350115000	11.500	0.4528			1	53.34
9002350120000	12.000	0.4724			1	53.34
9002350121000	12.100	0.4764			1	86.46
9002350123000	12.300	0.4843	31/64		1	60.03
9002350125000	12.500	0.4921			1	60.03
9002350127000	12.700	0.5000	1/2		1	60.03
9002350130000	13.000	0.5118			1	60.03

Series # 245 (D)

HSS general purpose (Type N), standard length, 5xD, 118° point, Morse Taper shank, steam oxide

EDP Number	Diameter				List Price	
	mm	decimal inch	fraction inch	wire/ letter	Pkg. Qty.	per piece
9002450023800	2.380	0.0937	3/32		1	28.25
9002450025000	2.500	0.0984			1	26.83
9002450027800	2.780	0.1094	7/64		1	26.83
9002450031700	3.170	0.1248	1/8		1	20.85
9002450035700	3.570	0.1406	9/64	28	1	27.59
9002450038000	3.800	0.1496		25	1	34.35
9002450039700	3.970	0.1563	5/32		1	18.77
9002450040000	4.000	0.1575			1	20.85
9002450042500	4.250	0.1673			1	27.59
9002450043700	4.370	0.1720	11/64		1	18.77
9002450045000	4.500	0.1772		16	1	18.77
9002450047600	4.760	0.1874	3/16		1	18.77
9002450050000	5.000	0.1969			1	18.77
9002450051000	5.100	0.2008			1	26.83
9002450051600	5.160	0.2031	13/64		1	18.77
9002450052000	5.200	0.2047			1	26.83
9002450052500	5.250	0.2067			1	31.58
9002450053000	5.300	0.2087			1	26.83
9002450054000	5.400	0.2126			1	26.83
9002450055000	5.500	0.2165			1	18.77
9002450055600	5.560	0.2189	7/32		1	18.77
9002450056000	5.600	0.2205			1	26.83
9002450057000	5.700	0.2244			1	26.83
9002450057500	5.750	0.2264			1	33.67

Series # 245 (D)

HSS general purpose (Type N), standard length, 5xD, 118° point, Morse Taper shank, steam oxide

EDP Number	Diameter				List Price	
	mm	decimal inch	fraction inch	wire/ letter	Pkg. Qty.	per piece
9002450058000	5.800	0.2283			1	26.83
9002450059000	5.900	0.2323			1	26.83
9002450059500	5.950	0.2343	15/64		1	18.77
9002450060000	6.000	0.2362			1	18.77
9002450061000	6.100	0.2402			1	26.83
9002450062000	6.200	0.2441			1	26.83
9002450062500	6.250	0.2461		D	1	33.67
9002450063000	6.300	0.2480			1	26.83
9002450063500	6.350	0.2500	1/4	E	1	18.77
9002450064000	6.400	0.2520			1	26.83
9002450065000	6.500	0.2559			1	18.77
9002450066000	6.600	0.2598			1	26.83
9002450067000	6.700	0.2638			1	26.83
9002450067500	6.750	0.2657	17/64	H	1	18.77
9002450068000	6.800	0.2677			1	26.83
9002450069000	6.900	0.2717		I	1	26.83
9002450070000	7.000	0.2756			1	18.77
9002450071400	7.140	0.2811	9/32	K	1	24.13
9002450072000	7.200	0.2835			1	26.83
9002450072500	7.250	0.2854			1	33.67
9002450073000	7.300	0.2874			1	26.83
9002450074000	7.400	0.2913			1	26.83
9002450075000	7.500	0.2953			1	18.77
9002450075400	7.540	0.2969	19/64		1	18.77
9002450076000	7.600	0.2992			1	30.30
9002450077000	7.700	0.3031			1	30.30
9002450077500	7.750	0.3051			1	33.67
9002450078000	7.800	0.3071			1	30.30
9002450079000	7.900	0.3110			1	30.30
9002450079400	7.940	0.3126	5/16		1	18.77
9002450080000	8.000	0.3150			1	18.77
9002450081000	8.100	0.3189			1	26.83
9002450082000	8.200	0.3228		P	1	26.83
9002450082500	8.250	0.3248			1	26.83
9002450083000	8.300	0.3268			1	26.83
9002450083300	8.330	0.3280	21/64		1	18.77
9002450084000	8.400	0.3307			1	26.83
9002450085000	8.500	0.3346			1	18.77
9002450086000	8.600	0.3386			1	26.83
9002450087000	8.700	0.3425			1	26.83
9002450087300	8.730	0.3437	11/32		1	20.21
9002450087500	8.750	0.3445			1	26.83
9002450088000	8.800	0.3465			1	26.83
9002450089000	8.900	0.3504			1	26.83
9002450090000	9.000	0.3543			1	18.77
9002450091000	9.100	0.3583			1	30.30
9002450091300	9.130	0.3594	23/64		1	20.85
9002450092000	9.200	0.3622			1	30.30
9002450092500	9.250	0.3642			1	30.30
9002450093000	9.300	0.3661			1	30.30
9002450094000	9.400	0.3701			1	30.30
9002450095000	9.500	0.3740			1	20.85
9002450095200	9.520	0.3748	3/8		1	20.85
9002450097000	9.700	0.3819			1	30.30
9002450097500	9.750	0.3839			1	30.30
9002450098000	9.800	0.3858		W	1	30.30
9002450099000	9.900	0.3898			1	30.30
9002450099200	9.920	0.3906	25/64		1	24.13
9002450100000	10.000	0.3937			1	20.85
9002450101000	10.100	0.3976			1	30.30
9002450102000	10.200	0.4016			1	24.13
9002450102500	10.250	0.4035			1	30.30
9002450103000	10.300	0.4055			1	30.30

DRILLING