

DRILLS

GUHRING

Series # 301 (D)

Cobalt Micro-Precision (Type N), micro-precision, 118° point,
reinforced straight shank, bright

EDP Number	Diameter				List Price	
	mm	decimal inch	fraction inch	wire/ letter	Pkg. Qty.	per piece
9003010002400	0.240	0.0094		88	10	7.72
9003010002450	0.245	0.0096			10	10.88
9003010002500	0.250	0.0098		87	10	7.72
9003010002550	0.255	0.0100			10	10.88
9003010002600	0.260	0.0102			10	7.72
9003010002650	0.265	0.0104			10	10.88
9003010002700	0.270	0.0106		86	10	7.72
9003010002750	0.275	0.0108			10	10.88
9003010002800	0.280	0.0110		85	10	7.72
9003010002900	0.290	0.0114		84	10	7.72
9003010002950	0.295	0.0116			10	10.88
9003010003000	0.300	0.0118			10	7.72
9003010003050	0.305	0.0120			10	10.88
9003010003100	0.310	0.0122		83	10	7.72
9003010003150	0.315	0.0124			10	10.88
9003010003200	0.320	0.0126		82	10	7.72
9003010003250	0.325	0.0128			10	10.88
9003010003300	0.330	0.0130		81	10	7.72
9003010003400	0.340	0.0134		80	10	7.72
9003010003450	0.345	0.0136			10	10.88
9003010003500	0.350	0.0138			10	7.72
9003010003550	0.355	0.0140			10	10.88
9003010003600	0.360	0.0142			10	7.72
9003010003650	0.365	0.0144			10	10.88
9003010003700	0.370	0.0146		79	10	7.72
9003010003750	0.375	0.0148			10	10.88
9003010003800	0.380	0.0150			10	7.72
9003010003850	0.385	0.0152			10	10.88
9003010003900	0.390	0.0154			10	7.72
9003010004000	0.400	0.0157	1/64		10	7.72
9003010004050	0.405	0.0159			10	10.88
9003010004100	0.410	0.0161		78	10	7.72
9003010004150	0.415	0.0163			10	10.88
9003010004200	0.420	0.0165			10	7.72
9003010004250	0.425	0.0167			10	9.31
9003010004300	0.430	0.0169			10	7.72
9003010004320	0.432	0.0170			10	9.31
9003010004400	0.440	0.0173			10	7.72
9003010004450	0.445	0.0175			10	9.31
9003010004500	0.450	0.0177			10	7.72
9003010004600	0.460	0.0181		77	10	7.72
9003010004700	0.470	0.0185			10	7.72
9003010004750	0.475	0.0187			10	9.31
9003010004800	0.480	0.0189			10	7.72
9003010004850	0.485	0.0191			10	9.31
9003010004900	0.490	0.0193			10	7.72
9003010004950	0.495	0.0195			10	9.31
9003010005000	0.500	0.0197			10	7.72
9003010005050	0.505	0.0199			10	9.31
9003010005100	0.510	0.0201		76	10	7.72
9003010005150	0.515	0.0203			10	9.31
9003010005200	0.520	0.0205			10	7.72
9003010005250	0.525	0.0207			10	9.31
9003010005300	0.530	0.0209		75	10	7.72
9003010005350	0.535	0.0211			10	9.31
9003010005400	0.540	0.0213			10	7.72
9003010005450	0.545	0.0215			10	9.31
9003010005500	0.550	0.0217			10	7.72
9003010005550	0.555	0.0219			10	9.31
9003010005600	0.560	0.0220			10	7.72
9003010005700	0.570	0.0224		74	10	7.72
9003010005800	0.580	0.0228			10	7.72

Series # 301 (D)

Cobalt Micro-Precision (Type N), micro-precision, 118° point,
reinforced straight shank, bright

EDP Number	Diameter				List Price	
	mm	decimal inch	fraction inch	wire/ letter	Pkg. Qty.	per piece
9003010005850	0.585	0.0230			10	9.31
9003010005900	0.590	0.0232			10	7.72
9003010005950	0.595	0.0234			10	9.31
9003010006000	0.600	0.0236			10	7.72
9003010006050	0.605	0.0238			10	9.31
9003010006100	0.610	0.0240		73	10	7.72
9003010006150	0.615	0.0242			10	9.31
9003010006200	0.620	0.0244			10	7.72
9003010006250	0.625	0.0246			10	7.72
9003010006300	0.630	0.0248			10	7.72
9003010006320	0.632	0.0249			10	9.31
9003010006400	0.640	0.0252		72	10	7.72
9003010006500	0.650	0.0256			10	7.72
9003010006550	0.655	0.0258			10	9.31
9003010006600	0.660	0.0260		71	10	7.72
9003010006650	0.665	0.0262			10	7.72
9003010006700	0.670	0.0264			10	7.72
9003010006750	0.675	0.0266			10	9.31
9003010006800	0.680	0.0268			10	7.72
9003010006900	0.690	0.0272			10	7.72
9003010007000	0.700	0.0276			10	7.72
9003010007050	0.705	0.0278			10	7.72
9003010007100	0.710	0.0280		70	10	7.72
9003010007200	0.720	0.0283			10	7.72
9003010007250	0.725	0.0285			10	9.31
9003010007300	0.730	0.0287			10	7.72
9003010007400	0.740	0.0291		69	10	7.72
9003010007500	0.750	0.0295			10	7.72
9003010007600	0.760	0.0299			10	7.72
9003010007700	0.770	0.0303			10	7.72
9003010007800	0.780	0.0307			10	7.72
9003010007900	0.790	0.0311	1/32	68	10	7.72
9003010007950	0.795	0.0313			10	9.31
9003010008000	0.800	0.0315			10	7.72
9003010008100	0.810	0.0319		67	10	11.32
9003010008200	0.820	0.0323			10	11.32
9003010008300	0.830	0.0327			10	11.32
9003010008400	0.840	0.0331		66	10	11.32
9003010008500	0.850	0.0335			10	7.72
9003010008600	0.860	0.0339			10	11.32
9003010008700	0.870	0.0343			10	11.32
9003010008800	0.880	0.0346			10	11.32
9003010008900	0.890	0.0350		65	10	11.32
9003010009000	0.900	0.0354			10	7.72
9003010009100	0.910	0.0358		64	10	11.32
9003010009200	0.920	0.0362			10	11.32
9003010009250	0.925	0.0364			10	11.32
9003010009300	0.930	0.0366			10	11.32
9003010009400	0.940	0.0370		63	10	11.32
9003010009500	0.950	0.0374			10	7.72
9003010009600	0.960	0.0378			10	11.32
9003010009700	0.970	0.0382		62	10	11.32
9003010009800	0.980	0.0386			10	11.32
9003010009900	0.990	0.0390		61	10	11.32
9003010010000	1.000	0.0394			10	7.72
9003010010100	1.010	0.0398			10	11.32
9003010010200	1.020	0.0402		60	10	11.32
9003010010300	1.030	0.0406			10	11.32
9003010010400	1.040	0.0409		59	10	11.32
9003010010500	1.050	0.0413			10	7.72
9003010010550	1.055	0.0415			10	11.32
9003010010600	1.060	0.0417			10	11.32

DRILLING